

SIMATIC S7-200, CPU 226 COMPACT UNIT, AC POWER SUPPLY
 24 DI DC/16 DO RELAY, 16/24 KB CODE/10 KB DATA, 2
 PPI/FREEPORT PORTS



Figure similar

Supply voltage	
Rated value (AC)	
• 120 V AC	Yes
• 230 V AC	Yes
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	5 V
• permissible range, upper limit (DC)	30 V
Load voltage L1	
• Rated value (AC)	100 V; 100 V AC to 230 V AC
• permissible range, lower limit (AC)	5 V
• permissible range, upper limit (AC)	250 V
• permissible frequency range, lower limit	47 Hz
• permissible frequency range, upper limit	63 Hz
Input current	
Inrush current, max.	20 A; at 264 V

from supply voltage L1, max.	320 mA; 40 to 160 mA (240 V); 80 to 320 mA (120 V); output current for expansion modules (5 V DC) 1000 mA
------------------------------	---

Encoder supply

24 V encoder supply	
• 24 V	Yes; Permissible range: 20.4V to 28.8V
• Short-circuit protection	Yes; electronic at 400 mA
• Output current, max.	400 mA

Memory

Number of memory modules (optional)	1; pluggable memory module, content identical with integral EEPROM; can additionally store recipes, data logs and other files
-------------------------------------	---

Work memory

• integrated (for program)	24 kbyte; 16 KB with active run-time edit
• integrated (for data)	10 kbyte

Backup

• present	Yes; Program: Entire program maintenance-free on integral EEPROM, programmable via CPU; data: Entire DB 1 loaded from PG/PC maintenance-free on integral EEPROM, current values of DB 1 in RAM, retentive memory bits, timers, counters, etc. maintenance-free via high-performance capacitor; optional battery for long-term buffering
-----------	---

Battery

Backup battery	
• Backup time, max.	100 h; (min. 70 h at 40 °C); 200 days (typ.) with optional battery module

CPU processing times

for bit operations, max.	0.22 µs
--------------------------	---------

Counters, timers and their retentivity

S7 counter

• Number	256
of which retentive with battery	
— can be set	Yes; via high-performance capacitor or battery
— lower limit	1
— upper limit	256

Counting range

— lower limit	0
— upper limit	32 767

S7 times

• Number	256
of which retentive with battery	
— adjustable	Yes; via high-performance capacitor or battery
— upper limit	64

Time range	
— lower limit	1 ms
— upper limit	54 min; 4 timers: 1 ms to 30 s; 16 timers: 10 ms to 5 min; 236 timers: 100 ms to 54 min

Data areas and their retentivity

Flag	
• Number, max.	32 byte
• Retentivity available	Yes; M 0.0 to M 31.7
• of which retentive with battery	0 to 255, via high-performance capacitor or battery, adjustable
• of which retentive without battery	0 to 112 in EEPROM, adjustable

Hardware configuration

Number of expansion units, max.	7; Only expansion modules of the S7-22x series can be used. Due to the limited output current, the use of expansion modules may be limited.
connectable programming devices/PCs	SIMATIC PG/PC, standard PC
Expansion modules	
• Analog inputs/outputs, max.	35; max. 28 inputs and 7 outputs (EM) or max. 0 inputs and 14 outputs (EM)
• Digital inputs/outputs, max.	148; max. 128 inputs and 120 outputs (CPU+EM)
• AS-Interface inputs/outputs, max.	62; AS-Interface A/B slaves (CP 243-2)

Digital inputs

Number of digital inputs	24
Source/sink input	Yes; optionally, per group
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	0 to 5 V
• for signal "1"	min. 15 V
Input current	
• for signal "1", typ.	2.5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; all
— at "0" to "1", min.	0.2 ms
— at "0" to "1", max.	12.8 ms
for interrupt inputs	
— parameterizable	Yes; I 0.0 to I 0.3
for counter/technological functions	
— parameterizable	Yes; (E 0.0 to E 1.5) 30 kHz
Cable length	
• shielded, max.	500 m; Standard input: 500 m, high-speed counters: 50 m
• unshielded, max.	300 m; not for high-speed signals

Digital outputs	
Number of digital outputs	16; Relays
Short-circuit protection	No; to be provided externally
Switching capacity of the outputs	
<ul style="list-style-type: none"> with resistive load, max. 	2 A
<ul style="list-style-type: none"> on lamp load, max. 	200 W; 30 W with DC, 200 W with AC
Output voltage	
<ul style="list-style-type: none"> for signal "1", min. 	L+/L1
Output current	
<ul style="list-style-type: none"> for signal "1" rated value 	2 A
<ul style="list-style-type: none"> for signal "0" residual current, max. 	0 mA
Output delay with resistive load	
<ul style="list-style-type: none"> "0" to "1", max. 	10 ms; all outputs
<ul style="list-style-type: none"> "1" to "0", max. 	10 ms; all outputs
Parallel switching of two outputs	
<ul style="list-style-type: none"> for uprating 	No
Switching frequency	
<ul style="list-style-type: none"> of the pulse outputs, with resistive load, max. 	1 kHz
Total current of the outputs (per group)	
all mounting positions	
<ul style="list-style-type: none"> — up to 40 °C, max. 	10 A
horizontal installation	
<ul style="list-style-type: none"> — up to 55 °C, max. 	10 A
Relay outputs	
<ul style="list-style-type: none"> Number of relay outputs, integrated 	16
<ul style="list-style-type: none"> Number of operating cycles, max. 	10 000 000; mechanically 10 million, at rated load voltage 100 000
Cable length	
<ul style="list-style-type: none"> shielded, max. 	500 m
<ul style="list-style-type: none"> unshielded, max. 	150 m
Analog inputs	
Number of analog potentiometers	2; Analog potentiometer; resolution 8 bit
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> 2-wire sensor 	Yes
<ul style="list-style-type: none"> — permissible quiescent current (2-wire sensor), max. 	1 mA
1. Interface	
Interface type	Integrated RS 485 interface
Physics	RS 485
Functionality	

- MPI Yes; As MPI slave for data exchange with MPI masters (S7-300/S7-400 CPUs, OPs, TDs, Push Button Panels); S7-200-internal CPU/CPU communication is possible in the MPI network with restrictions; transmission rates: 19.2/187.5 kbit/s
- PPI Yes; with PPI protocol for program functions, HMI functions (TD 200, OP), S7-200-internal CPU/CPU communication ; transmission rates 9.6/19.2/187.5 kbit/s
- serial data exchange Yes; As freely programmable interface with interrupt facility for serial data exchange with third-party devices with ASCII protocol transfer rates: 1.2 / 2.4 / 4.8 / 9.6 / 19.2 / 38.4 / 57.6 / 115.2 kbit/s; the PC/PPI cable can also be used as RS232/RS485 converter

MPI	
• Transmission rate, min.	19.2 kbit/s
• Transmission rate, max.	187.5 kbit/s

2. Interface

Interface type	Integrated RS 485 interface
----------------	-----------------------------

Physics	RS 485
---------	--------

Functionality

- MPI Yes; As MPI slave for data exchange with MPI masters (S7-300/S7-400 CPUs, OPs, TDs, Push Button Panels); S7-200-internal CPU/CPU communication is possible in the MPI network with restrictions; transmission rates: 19.2/187.5 kbit/s
- PPI Yes; with PPI protocol for program functions, HMI functions (TD 200, OP), S7-200-internal CPU/CPU communication ; transmission rates 9.6/19.2/187.5 kbit/s
- serial data exchange Yes; As freely programmable interface with interrupt facility for serial data exchange with third-party devices with ASCII protocol transfer rates: 1.2 / 2.4 / 4.8 / 9.6 / 19.2 / 38.4 / 57.6 / 115.2 kbit/s; the PC/PPI cable can also be used as RS232/RS485 converter

MPI	
• Transmission rate, min.	19.2 kbit/s
• Transmission rate, max.	187.5 kbit/s

Integrated Functions

Number of counters	6; High-speed counters (30 kHz each), 32 bits (incl. sign), can be used as up/down counters or for connecting 2 incremental encoders with 2 pulse trains offset by 90° (max. 20 kHz (A/B counters)); parameterizable enable and reset input; interrupt facilities (incl. call of subroutine with any content) when the setpoint is reached; reversal in counting direction, etc.
Counting frequency (counter) max.	30 kHz
Number of alarm inputs	4; 4 rising edges and/or 4 falling edges

Potential separation

Potential separation digital inputs	
• between the channels	Yes; Optocoupler
• between the channels, in groups of	13 and 11

Potential separation digital outputs	
<ul style="list-style-type: none"> • between the channels • between the channels, in groups of 	<p>Yes; Relays</p> <p>4, 5 and 7</p>
Permissible potential difference	
between different circuits	500 V DC between 24 V DC and 5 V DC; 1500 V AC between 24 V DC and 230 V AC
Degree and class of protection	
Degree of protection acc. to EN 60529	
<ul style="list-style-type: none"> • IP20 	Yes
Ambient conditions	
Environmental conditions	For further environmental conditions, see "Automation System S7-200, System Manual"
Ambient temperature during operation	
<ul style="list-style-type: none"> • horizontal installation, min. • horizontal installation, max. • vertical installation, min. • vertical installation, max. 	<p>0 °C</p> <p>55 °C</p> <p>0 °C</p> <p>45 °C</p>
Air pressure acc. to IEC 60068-2-13	
<ul style="list-style-type: none"> • permissible range, lower limit • permissible range, upper limit 	<p>860 hPa</p> <p>1 080 hPa</p>
Relative humidity	
<ul style="list-style-type: none"> • Operation, min. • Operation, max. 	<p>5 %</p> <p>95 %; RH class 2 in accordance with IEC 1131-2</p>
Configuration	
Programming	
<ul style="list-style-type: none"> • Command set • Program processing • Program organization • Number of subroutines, max. 	<p>Bit logic instructions, compare instructions, timer instructions, counter instructions, clock instructions, transmissions instructions, table instructions, logic instructions, shift and rotate instructions, conversion instructions, program control instructions, interrupt and communications instructions, logic stack instructions, integer maths, floating-point math instructions, numerical functions</p> <p>free cycle (OB 1), interrupt-controller, time-controlled (1 to 255 ms)</p> <p>1 OB, 1 DB, 1 SDB subroutines with/without parameter transfer</p> <p>64</p>
Programming language	
<ul style="list-style-type: none"> — LAD — FBD — STL 	<p>Yes</p> <p>Yes</p> <p>Yes</p>
Know-how protection	
<ul style="list-style-type: none"> • User program protection/password protection 	Yes; 3-stage password protection

Connection method

Plug-in I/O terminals	Yes
-----------------------	-----

Dimensions

Width	196 mm
-------	--------

Height	80 mm
--------	-------

Depth	62 mm
-------	-------

Weights

Weight, approx.	660 g
-----------------	-------

last modified:	09/10/2016
-----------------------	------------